

809H Series – 316L SS OEM Pressure Transducer

- ▶ Sensing Ranges from 0 to 1,000 psi (0 to 69 bar)
- ▶ Rugged Stainless Steel & Valox® Housings
- ▶ Ideal for High Shock & Vibration Applications
- ▶ Non-Oil-Filled Design
- ▶ Ideal for Alternative Energy Market

The 809H Series pressure transducers are designed specifically for industrial applications with demanding price and performance requirements. They offer exceptional reliability in typical industrial grade environments. 809H Series transducers operate on low-cost, unregulated DC power, and over a wide temperature band with both liquids and gases. Designed for harsh environments, they are suitable for use in high shock and vibration applications. Stainless steel and Valox® housings are small and lightweight for easy integration into compact systems. The standard feature set of the 809H Series delivers exceptional performance in extreme environmental conditions at a price that OEMs will appreciate.

Common Specifications

Input	
Pressure Range	0 to 1,000 psi (0 to 69 bar)
Proof Pressure	See ordering chart
Burst Pressure	See ordering chart
Fatigue Life	>1 million cycles
Performance	
Supply Voltage (Vs)	9-30 VDC (5 VDC on 0.5-4.5 VDC units)
Long Term Drift	0.5% FS/year
Accuracy	±0.25% FS
Thermal Error Zero	±0.02% FS/°F (±0.036% FS/°C)
Thermal Error Span	±0.015% FS/°F (±0.030% FS/°C)
Compensated Temperatures	-4°F to +176°F (-20°C to +80°C)
Operating Temperatures	-40°F to +185°F (-40°C to +85°C)
Storage Temperatures	-40°F to +185°F (-40°C to +85°C)
Zero Tolerance	1% of span
Span Tolerance	1% of span
Response Time	5 ms
Mechanical Configuration	
Pressure Port	See ordering chart
Wetted Parts	316L Stainless Steel
Electrical Connection	See Dimensions chart, next page
Enclosure	Weather-Resistant (Stainless Steel and Valox®)
Vibration	20g (MIL STD 202, Method 204, Condition C)
Shock	200g (MIL STD 202, Method 213B, Condition C)
Weight	3.1 oz (88 grams), approx.

Individual Specifications

Voltage Output Units	
Output	3 Wire, see ordering chart
Current Consumption	8 mA
Min. Load Resistance	5000 ohms
Current Output Units	
Output	4-20 mA (2 wire)
Max. Loop Resistance	(Vs-9) x 50 ohms



1/2" Conduit



Cable



3-Pin Packard Connector



Hirschmann Connector

Applications

- Hydraulic Systems
- Compressor Control
- HVAC/R Equipment
- Industrial Engines
- Process and Containerized Refrigeration Systems
- Industrial OEM Equipment

How They Operate

809 Series transducers utilize a proven center mount electrode configuration combined with a durable 316L stainless steel pressure sensing element to form a variable capacitor. As pressure (or vacuum) increases or decreases, the capacitance changes. Self-contained high-level output IC-circuitry converts the change in capacitance to a fully conditioned linear voltage or current output signal.

Dimensions

Electrical Termination Style	Cable Anchor	1/2" Conduit	Hirschmann Connector	3-Pin Packard Connector
Terminal Specifications	Standard: 2 ft. multiconductor cable. Longer lengths options. See ordering chart.	1/2" conduit connection with 3-screw terminal block.	Mating connector is Hirschmann G4WIF. May be ordered separately from Gems— Option 590.	Mating connector is comprised of Packard P/Ns 12065287 & 12103881. May be ordered separately from Gems— Option 581/582.
Ordering Code	XX (cable length in feet)	A1 - Conduit	H2	P1 (3-Pin)

How to Order

Use the **bold** characters from the chart below to construct a product code.

SELECT

809H - 025P - G - 2M - 11 - 02 - XXX

Series **809H** - 809H Series

Pressure Range Code

Pressures – psi

Code	Range	Proof	Burst	Code	Range	Proof	Burst
025P*	0 to 25	40	300	250P*	0 to 250	350	1500
050P*	0 to 50	75	500	500P*	0 to 500	700	2000
100P*	0 to 100	150	750	10CP*	0 to 1000	1300	3000

Note: Compound ranges are available upon request

Datum

- G** - Gauge
- S** - Sealed (available in 250 psi ranges and above)

Options

- 590** - Hirschmann Mating Connector (for H2 Termination)
- 581** - Packard Mating Connector, 3 ft. (for P1 Termination)
- 582** - Packard Mating Connector, 6 ft. (for P1 Termination)

Electrical Termination

- XX** - Cable length in feet (e.g., 02 = 2 ft.)*
- P1** - Packard (3-Pin)
- H2** - Hirschmann ("Mini")
- A1** - 7/8" Hole for 1/2" Conduit*

Output

- 11** - 4-20 mA*
- 23** - 0.2 to 5.2 VDC
- 24** - 0.5-5.5 VDC*

Pressure Port

- 2M** - 1/4" NPT Male*
- J7** - 7/16" SAE Male (J1926-2)
- 1M** - 1/8" NPT Male

* Standard configuration. Minimum 25 pieces apply for all other configurations.