

 <p><b>Photocopy This Form</b> Use one form for each product type you are selecting. <small>This form may also be completed online at gemssensors.com for RFQ.</small></p>	This is a <input type="checkbox"/> Request for a Quote <input type="checkbox"/> Order P.O.# _____ Quantity Needed _____ Date Required ____/____/____ Shipping Method: _____ Partial Accepted: <input type="checkbox"/> Yes <input type="checkbox"/> No	Name _____ Company _____ Street _____ City _____ State ____ Zip _____ Phone (____) _____ Fax (____) _____
---	--	--

## SureSite Indicators, Alloy Versions – Standard Size

### Process Conditions

This information is essential to the accurate and proper operation of your SureSite® Visual Level Indicators. Please complete fully and accurately.

- |  |   |
|--|---|
| <b>1. Pressure:</b> Operating _____ psig Maximum _____ psig<br><b>2. Temperature:</b> Operating _____ °F Maximum _____ °F<br><b>3. Liquid Media:</b> _____ | <b>4. Specific Gravity @ Operating Condition:</b> _____<br><b>5. Viscosity:</b> _____ SSU<br><b>6. Application Location:</b> <input type="checkbox"/> Indoors <input type="checkbox"/> Outdoors |
|--|---|

### Physical Configuration

#### 1. Mounting Configuration Types:

- Type AA     Type BA     Type CA     Type DA

#### 2. Housing and Float Material

- Code 2     Code 3     Code 4

#### 3. Connection Codes – Complete all 4 connection code lines. Check off NPT or Flange size where appropriate.

▼ Connection Code Number Goes Here. **Connection Code Numbers and their descriptions are on Page D-8.**

Top T	NPT	Flange			
	<input type="checkbox"/> 1/2" <input type="checkbox"/> 1" <input type="checkbox"/> 2" <input type="checkbox"/> Other _____	<input type="checkbox"/> 1/2" <input type="checkbox"/> 1" <input type="checkbox"/> 2" <input type="checkbox"/> Other _____	<input type="checkbox"/> 150# (RF) <input type="checkbox"/> 600# (RF) <input type="checkbox"/> Other _____		
Side Sa	NPT	Flange			
	<input type="checkbox"/> 1/2" <input type="checkbox"/> 1" <input type="checkbox"/> 2" <input type="checkbox"/> Other _____	<input type="checkbox"/> 1/2" <input type="checkbox"/> 1" <input type="checkbox"/> 2" <input type="checkbox"/> Other _____	<input type="checkbox"/> 150# (RF) <input type="checkbox"/> 600# (RF) <input type="checkbox"/> Other _____		
Side Sb	NPT	Flange			
	<input type="checkbox"/> 1/2" <input type="checkbox"/> 1" <input type="checkbox"/> 2" <input type="checkbox"/> Other _____	<input type="checkbox"/> 1/2" <input type="checkbox"/> 1" <input type="checkbox"/> 2" <input type="checkbox"/> Other _____	<input type="checkbox"/> 150# (RF) <input type="checkbox"/> 600# (RF) <input type="checkbox"/> Other _____		
Bottom B	NPT	Flange			
	<input type="checkbox"/> 1/2" <input type="checkbox"/> 1" <input type="checkbox"/> 2" <input type="checkbox"/> Other _____	<input type="checkbox"/> 1/2" <input type="checkbox"/> 1" <input type="checkbox"/> 2" <input type="checkbox"/> Other _____	<input type="checkbox"/> 150# (RF) <input type="checkbox"/> 600# (RF) <input type="checkbox"/> Other _____		

- 4. Length of Visual Indication – L:** \_\_\_\_\_ inches (240", Max.).  
 Connection to Connection Dimension – C to C: \_\_\_\_\_ inches.

#### 5. Flag Type

- Plastic flags available to 300°F (149°C).  
 Aluminum flags only for temperatures to 750°F (399°C).  
 Plastic (Orange and White)     Aluminum (Black and Silver)  
 Non-Standard; Specify: \_\_\_\_\_ consult factory.

#### Special Instructions (Materials, Connections, etc.)

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

### Accessories (Pages D-16 to D-18)

- 1. Transmitters (Continuous Electrical Indication):**  
 Low Temperature – 300°F (149°C)     Explosion-Proof  
 High Temperature – 750°F (399°C)
- 2. J-Box/Signal Conditioners Accessories:**  
 Terminal Strip     4-20 mA Output  
 0-12 VDC Output     0-5 VDC Output
- 3. Power Supply:**     115 VAC (Input) /24 VDC (Output) (Optional)  
 230 VAC (Input) /24 VDC (Output)

- 4. Switch Modules (Single Point):** \_\_\_\_\_ Quantity (only if required)  
 a.  SPST    SPDT    DPDT 120 VAC    DPDT 24 VDC  
 b.  Standard – 300°F (149°C)     Explosion Proof  
 High Temperature – 750°F (399°C)

#### 5. Indicating Scales:

- Feet and Inches     Inches     Metric     Blank  
 Custom Graduations; specify: \_\_\_\_\_

Please contact GEMS Sensors Inc. for any configuration or special requirements not covered on this form. **800-378-1600**

Quote: \$ \_\_\_\_\_ Date Quoted: \_\_\_\_/\_\_\_\_/\_\_\_\_



**Gems Sensors & Controls**  
 One Cowles Road  
 Plainville, CT  
 06062-1198

tel 860.747.3000  
 fax 860.747.4244  
 www.gemssensors.com